CLAIMS

WE CLAIM:

- 1. (Original) A system for processing biosolids from a sludge pond into fertilizer comprising:
- (a) a portable dewatering system for removing liquid from sludge, said portable dewatering system having:
- a collection device for collecting sludge from said sludge pond;
- a centrifuge for removing liquids from said sludge collected by said collection device to create a biosolids composition; and
- a transfer device to transfer said biosolids composition from said centrifuge;
- (b) a transport vehicle for receiving said biosolids composition from said transport device, said transport vehicle transporting said biosolids from said sludge pond to a fixed processing plant; and
 - (c) the fixed processing plant having:
- a mixer for mixing a stabilizing agent with said biosolids composition to create mixed biosolids;
- a heating and sterilising system to heat and sterilize the mixed biosolids and for extruding sterilized pellets; and
 - a drying system for drying the pellets, wherein said pellets can be used as fertilizer.
- 2. (Original) The system of claim 1, wherein said portable dewatering system is mounted on a truck.
- 3. (Original) The system of claim 1, wherein said collection device is a pump.
- 4. (Original) The system of claim 1, wherein said collection device is a dredge.

- 5. (Original) The system of claim 3, wherein said transfer device is a conveyor.
- 6. (Original) The system of claim 5, wherein said portable dewatering system, further comprising a generator to power said pump, centrifuge and conveyor.
- 7. (Original) The system of claim 6, wherein said portable dewatering system further comprises a holding tank for holding sludge collected by said pump.
- 8. (Original) The system of claim 7, wherein said portable dewatering system further comprising a step screen between said holding tank and said centrifuge to remove debris from said sludge.
- 9. (Original) The system of claim 8, wherein said step screen includes an auger drive.
- 10. (Original) The system of claim 1, wherein said biosolids composition includes 25% solids.
- 11. (Original) The system of claim 1, wherein said heating and sterilizing system is a microwave extruder.
- 12. (Original) The system of claim 11, wherein said microwave extruder includes:
- a loading hopper for receiving mixed biosolids; an extruder screw for conveying mixed biosolids from said loading hopper;
- a microwave source for heating said mixed biosolids along said extruder screw.

- 13. (Original) The system of claim 12, wherein said processing plant further includes an ultraviolet treatment device for treating said mixed biosolids.
- 14. (Original) The system of claim 13, wherein said processing plant further includes an ammonia recovery device to recover ammonia from said mixed biosolids.

15.-28. (Cancelled)